


REFERENCE COPY



TECHNICAL NOTE No. 842
AFSWP NO 767

REFERENCE COPY
DOES NOT CIRCULATE

Records of Air Shock Loading On A Three Dimensional Model

GLENN P. BEICHLER

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21006

DEPARTMENT OF THE ARMY PROJECT Nos. 598-09-003 AND 503-04-002
ORDNANCE RESEARCH AND DEVELOPMENT PROJECT No. TB3-0112

The Ballistic Research Laboratories Technical Note is designed for use within the laboratories or for issuing available information, when the occasion demands speed.

The contents of this paper are of the nature of advance information and may be extended or otherwise revised.

BALLISTIC RESEARCH LABORATORIES



ABERDEEN PROVING GROUND, MARYLAND

BALLISTIC RESEARCH LABORATORIES

TECHNICAL NOTE NO. 842

JANUARY 1954

RECORDS OF AIR SHOCK LOADING ON A THREE
DIMENSIONAL MODEL

Glenn P. Beichler

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21005

Department of the Army Project Nos. 598-09-003
and 503-04-002
Ordnance Research and Development Project No. TB3-0112

Funds for this work were provided by the Armed Forces
Special Weapons Project as a part of Operation Upshot-
Knothole Project 3.28.1

ABERDEEN PROVING GROUND, MARYLAND

BALLISTIC RESEARCH LABORATORIES

TECHNICAL NOTE NO. 842

GPBeichler/ddh
Aberdeen Proving Ground, Md.
January 1954

RECORDS OF AIR SHOCK LOADING ON A THREE
DIMENSIONAL MODEL

ABSTRACT

Tracings are presented of the original records of air blast loading obtained in the 24-inch BRL shock tube on the front, top and rear surfaces of a rectangular shaped three-dimensional model. The records were obtained at incident shock pressures of approximately 3, 5 and 8 psi using a 2" x 4" x 2" "Oilite" model. Since essentially, the variations in loading are over in less than one millisecond the incident shock wave is a step shock.

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21005

INTRODUCTION

A primary objective for the Ballistic Research Laboratories Shock Tube Facility has been to reduce to a routine operation the obtaining of accurate blast loading data on three-dimensional models. This has been done on a series of models for Ballistic Research Laboratories AFSWP Project 3.28.1. The results on the first model of this series are presented here. While the work presented here does not represent the ultimate perfection of the art nor even a fair example of the far more advanced present state of measurement techniques, it is a typical series of curves which may be useful to others in interpreting field data or theoretical work or, perhaps, in planning future model work for the shock tube. No analysis of the records is attempted; no conclusions are drawn.

EXPERIMENTAL PROCEDURE

The Model

The 2" x 4" x 2" model was made of "Oilite", a highly compressed powdered metal made of copper and tin and impregnated with oil, in an effort to achieve some internal damping and consequent reduction of vibration. One 2" x 4" face was instrumented with five piezoelectric pressure gauges as shown in sketch 1. The model could then be oriented in the shock tube as this instrumented face is normal to the shock front, side-on, or facing away from the direction of shock wave approach. The model was mounted on a large flat plate extending across the shock tube in such a way that leads from the five gauges could be readily brought out from the tube.

The Gauges

The one-half inch overall diameter piezoelectric gauges were constructed with 0.2" diameter tourmaline crystal elements. Complete description of gauge design and construction may be found in BRL Technical Note No. 860 by C. Benjamin Granath. Recording was accomplished with the eight channel Armour oscillograph which in addition provided calibration and time measurements.


RESULTS

Pressure versus time curves are presented at five different points on the 2" x 4" front, top, and rear surfaces of a 2" x 4" x 2" three-dimensional model using incident step shock strengths of approximately 3, 5, and 8 psi. The position at which the pressure-time curve was taken is indicated in the little sketch adjacent to each curve. Incident pressure is also indicated for each curve as P_1 . For the short times presented, the incident pressure is essentially a constant. Rough pressure and time coordinates are indicated. Timing marks are in milliseconds. More precise measurements may be made by using the pressure and time factors given for each curve. For the pressure-time curves for the model top positions

the direction of approach of the shock wave is denoted by an arrow on the diagram and the approximate time of arrival of the shock at the front face is shown on the pressure-time curve with a caret (^).

GLENN P. BEICHLER

Glenn P Beichler



GAUGE POSITIONS 1 THRU 5

SKETCH 1
OILITE MODEL

TECHNICAL LIBRARY
AMXBR-LB (Bldg. 305)
ABERDEEN PROVING GROUND, MD. 21005

OLITE MODEL


POSITION 1

IMM = .305 PSI

IMM = .0170 MSEC.

P = 2.94

FRONT FACE




POSITION 2


IMM = .1625 PSI

IMM = .0170 MSEC.

P = 2.94

FRONT FACE






OILITE MODEL

POSITION 5

IMM = .0030 PSI
INM = .0174 MSEC
P_i = 2.38

FRONT FACE




OILITE MODEL

$\Delta P = 0.81 \text{ PSI}$
 $\Delta P = 0.170 \text{ M SEC.}$
 $P_1 = 3.30$

POSITION 1

BACK FACE

PRESSURE
PSI




$\Delta P = .103 \text{ PSI}$
 $\Delta P = .0173 \text{ M SEC.}$
 $P_1 = 3.30$

POSITION 2

BACK FACE

PRESSURE
PSI



OILITE MODEL

IMM = .0255 PSI
 IMM = .0172 MSEC.
 P_i = 2.44

POSITION 3

BACK FACE

C

PRESSURE
 PSI



TIME (MSEC.)


IMM = .0397 PSI
 IMM = .0172 MSEC.
 P_i = 2.44

POSITION 4

BACK FACE

•

PRESSURE
 PSI



TIME (MSEC.)

OILITE MODEL

POSITION 5

BACK FACE

IMM = 1118 PSI
IMM = 0.72 MSEC
 $P_1 = 2.44$



OILITE MODEL

POSITION 1

TOP FACE

IMM = .135 PSI
IMM = .022 MSEC.
 $P_1 = 2.31$

PRESSURE
PSI

3

1.5

0

TIME (MSEC)

2

POSITION 2

TOP FACE

IMM = .186
IMM = .022 MSEC.
 $P_1 = 2.31$

PRESSURE
PSI

3

1.5

0

TIME (MSEC)

2

A = INDICATES TIME SHOCK WAVE STRUCK MODEL

OILITE MODEL

POSITION 3

TOP FACE

$\Delta P = .143 \text{ PSI}$
 $\Delta P = .022 \text{ MSEC}$
 $P_1 = 2.31$

PRESSURE
PSI

3
1.5

0

TIME (M SEC)

2

POSITION 4

TOP FACE

$\Delta P = .15 \text{ PSI}$
 $\Delta P = .022 \text{ M SEC}$
 $P_1 = 2.31$

PRESSURE
PSI

3
1.5

0

TIME (M SEC)

2

OILITE MODEL

POSITION 5

TOP FACE

IMM = .15 PSI

IMM = .022 M/SEC

$P_1 = 2.31$

PRESSURE
PSI

3

1.5

0

TIME (M SEC)

2

Λ = INDICATES TIME SHOCK WAVE STRUCK MODEL


OIL TE MODEL

POSITION 1

FRONT FACE

IMM = .336 PSI
IMM = .0175 MSEC
 $P_i = 5.33$

PRESSURE
PSI




POSITION 2

FRONT FACE

IMM = .336 PSI
IMM = .0175 MSEC
 $P_i = 5.33$

PRESSURE
PSI




OILITE MODEL

POSITION 3

FRONT FACE


IMM = 322 PSI
IMM = .0175 M SEC.
 $P_i = 5.33$



POSITION 4

FRONT FACE

IMM = 412 PSI
IMM = .0175 M SEC.
 $P_i = 5.33$



OILITE MODEL

POSITION 5

FRONT FACE

LMM = 42.05 PSI

LMM = 0.75

$P_i = 5.33$


PRESSURE
PSI

15
12
9
6
3
0

TIME (MSEC)

1

2



OILITE MODEL

POSITION 1

BACK FACE

IMM = .082 PSI
IMM = .0174 MSEC.
 $P_1 = 5.5$

PRESSURE

PSI

5 -
3.75 -
2.5 -

TIME (MSEC)

1

2

POSITION 2

BACK FACE

IMM = .0893 PSI
IMM = .0172 MSEC.
 $P_1 = 5.5$

PRESSURE


PSI

5 -
3.75 -
2.5 -

TIME (MSEC)

1

2



OILITE MODEL

POSITION 5

BACK FACE

IMM = .112 PSI

IMM = .0185 MSEC

$P_1 = 5.08$

PRESSURE
PSI

5
3.75
2.5

TIME (MSEC)

1

2



OILITE MODEL

POSITION 1

TOP FACE

IMM = .164 PSI
IMM = .020 MSEC
 $P_1 = 4.34$



POSITION 2

TOP FACE

IMM = .189 PSI
IMM = .020 MSEC
 $P_1 = 4.34$



A = INDICATES TIME SHOCK WAVE STRUCK MODEL


OILITE MODEL

POSITION 3

TOP FACE

IMM = 0.969 PSI
IMM = 0.020 M SEC
 $P_1 = 4.34$


PRESSURE
PSI



POSITION 4

IMM = 1.17 PSI
IMM = 0.020 M SEC
 $P_1 = 4.34$

PRESSURE
PSI




Δ = INDICATES TIME SHOCK WAVE STRUCK MODEL

OILITE MODEL


POSITION 5

TOP FACE

IMM = .148 PSI
IMM = .022 MSEC.
 $P_1 = 4.34$



A = INDICATES TIME SHOCK WAVE STRUCK MODEL



OLITE MODEL

POSITION 3

FRONT FACE

MM = .264 PSI
MM = .0171 MSEC.
P_i = 6.09

PRESSURE
PSI

20

15

10

5

0

TIME (MSEC.)

2

POSITION 4

FRONT FACE

MM = .323 PSI
MM = .0174 MSEC.
P_i = 6.49

PRESSURE
PSI

20

15

10

5

0

TIME (MSEC.)

2

OLITE MODEL

POSITION 5

IMM = 26 (PSI)
IMM = 0.170 MSEC
P_i = 8.30

FRONT FACE

PRESSURE
PSI

20

15


10

5

0

2

TIME (MSEC)




OILITE MODEL

POSITION 1

BACK FACE

MM = 130 PSI
MM = 0.172 MSEC.
 $P_1 = 8.3$

PRESSURE
PSI




POSITION 2

BACK FACE

MM = 198 PSI
MM = 0.171 MSEC.
 $P_1 = 8.3$

PRESSURE
PSI



OILITE MODEL

POSITION 3

BACK FACE

IMM = .096 PSI
 IMM = 0.172 MSEC.
 $P_1 = 7.84$

PRESSURE
 PSI

TIME (MSEC.)

2

POSITION 4


BACK FACE


IMM = .114 PSI
 IMM = 0.172 MSEC.
 $P_1 = 7.84$


PRESSURE
 PSI

TIME (MSEC.)

2







OILITE MODEL

POSITION 5

TOP FACE

INM = .2038 PSI

INM = .022 M SEC

P = 9.01

PRESSURE
PSI

100
75
50
25

0

TIME (M SEC)

1
2

Δ • INDICATES TIME SHOCK WAVE STRUCK MODEL

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
4	Chief of Ordnance Department of the Army Washington 25, D.C. Attn: ORDTB - Bal Sec	1	Director of Intelligence United States Air Force Washington 25, D. C. Attn: Lt. Col. John W. Ault Deputy Director for Targets Physical Vulnerability Branch
4	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Re3	1	Commander Air Research and Development Command P. O. Box 1395 Baltimore 3, Maryland Attn: Lt. Col. D. L. Crowson
2	Commander Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland Attn: Explosives Division	1	Commanding Officer Air Force Cambridge Research Laboratory 230 Albany Street Cambridge, Massachusetts Attn: FRHS-1, Geophysical Research Library
1	Commander Naval Ordnance Test Station Inyokern P. O. China Lake, California Attn: Technical Library	1	Commander Air Materiel Command Wright-Patterson Air Force Base, Ohio Attn: MCAIDS
1	Director Naval Research Laboratory Anacostia Station Washington 20, D. C.	1	Diamond Ordnance Fuze Laboratories Connecticut Avenue at Van Ness St. N.W. Washington 25, D. C. Attn: Mr. Fred Harris, Division 20
1	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D. C. Attn: Code P-300	1	Director David Taylor Model Basin Washington 7, D. C. Attn: Structural Mechanics Division
1	Officer in Charge Naval Civil Engineering Research & Evaluation Laboratory Naval Station Port Hueneme, California		
1	Deputy Chief of Staff Development Research & Development Directorate United States Air Force Washington 25, D. C. Attn: Chief, Research Division		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
5	Armed Forces Special Weapons Project P. O. Box 2610 Washington 25, D. C. Attn: Blast Branch	1	Broadview Research & Development P. O. Box 1093 Burlingame, California Attn: Dr. Richard I. Condit
1	Chief of Engineers Department of the Army Washington 25, D. C. Attn: Mr. M. D. Kirkpatrick	1	Dr. John M. Richardson Institute of Industrial Research University of Denver Denver 10, Colorado
1	Commanding General Technical Command Army Chemical Center, Maryland	1	Dr. S. J. Fraenkel Division of Engineering Mechanics Armour Research Foundation Chicago 16, Illinois
2	Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico Attn: Dr. Fred Reines	1	Dr. R. J. Hansen Massachusetts Institute of Technology Cambridge 39, Massachusetts
5	Director Armed Services Technical Information Agency Documents Service Center Knott Building Dayton 2, Ohio Attn: DSC - SA	1	Dr. N. M. Newmark 111 Talbot Laboratory University of Illinois Urbana, Illinois
1	Director, Project RAND Department of the Air Force 1700 Main Street Santa Monica, California Attn: Mr. Marc Peter	1	Dr. Otto LaPorte Engineering Research Institute University of Michigan Ann Arbor, Michigan
1	Applied Physics Laboratory 8621 Georgia Avenue Silver Spring, Maryland	1	Dr. Walker Bleakney Princeton University Princeton, New Jersey
2	Sandia Corporation P. O. Box 5800 Albuquerque, New Mexico Attn: Physics Div. - Dr. E. Cox Blast Model Studies Div. Dr. J. Shreve	1	Dr. J. Kirkwood Department of Chemistry Yale University New Haven, Connecticut